




**RIVKLE® Steel blind rivet nuts/
Extending the RIVKLE® plus range**

Round body, plain, extra-small countersunk head

Type 343 01 for holes with imperial dimensions

Advantages:

- very small head projection without countersinking
- screw length can be varied



For the products shown in Blue we recommend the use of **RIVKLE® plus 343 67**, page 14, where there are holes with metric dimensions.

d	Thickness e	Hole D ^{+0.1/0}	B	E _{max.}	S*	L	L ₂ *	B 71 100 Product code
M3	0.5 – 1.5	4.7	5.2	0.4	S = 3-e	8.4	5.5	3430 103 0150
M4	0.5 – 2.0	6.4	6.7	0.5	S = 3.5-e	10.4	7.3	3430 104 0150
M5	0.5 – 3.0	7.1	7.5	0.6	S = 4.5-e	11.5	7.3	3430 105 0150
M6	0.7 – 3.0	9.5	10.2	0.6	S = 5.5-e	14.5	9.3	3430 106 0200
M8	0.8 – 4.5	10.5	11.3	0.7	S = 7.5-e	16.8	9.6	3430 108 0450

* Dimensions S and L₂ are indicative values. the difference in length S depends on the material thickness and is used as the setting tool stroke.

Dimensions in mm.

Surface treatment: 8 μ zinc plated + yellow passivated.

D = the imperial dimensions are expressed in mm.

Other dimensions and variants can be supplied on request.